




[About Us](#) | [Research & Development](#) | [Programs](#) | [Contact Us](#) | [CECSTR Home](#)

Welcome Today is Wed Sep 2 2009



CECSTR NEWS

CECSTR Seeks Industry Support

2008 Annual Report

Scholarship 2009-2010

Nov 12, 2009: Advisory Board Meeting

2007 Advisory Board Meeting in Photos

2006 Advisory Board Meeting in Photos


*A
National Resource in
Communication Systems
Technology Research
&
Education.....*

TAMU SYSTEM PATHWAY SYMPOSIUM, NOVEMBER 7-9, 2008

AWARD WINNING PROJECT - 1st PLACE (Graduate Division) **Programmable Dead-time and Phase-shift Digital Controller by Using FPGA**

Research Assistants (G): Chu Kuang Liu , Chao Xia
Advisors: Dr. SuXia Cui Dr. Yongpeng Zhang, and Dr. Cajetan M. Akujuobi

Synopsis: This project describes an engineering project with simulation for a digital control module of the DC/DC Phase-shift Full Bridge Converter by using FPGA (Field Programmable Gate Array) in Xilinx environment with VHDL codes. The digital control module is developed to control the dead-time (Td) to achieve the ZVS (Zero Voltage Transition) in the Full-Bridge DC/DC converters and it is also able to shift the phase of the PWMs (PWMA,PWMB,PWMC,PWMD) with Tf to adjust the duty-cycle of the DC/DC converter by feedback to regulate the output voltage. This digital control module with FPGA technology will be used on the future research for the digital-control power architecture as to compare the performance with other digital controllers (DSP ,Micro controller). (info>



Graduate RA: Chu Liu and Chao Xia

AWARD WINNING PROJECT - 2nd PLACE (UG- Division)
Evaluation of Coefficient of Friction of Thermal Battery Insulators
UG. RA: Taiwo Femi-Fowode, Fiona Obasuyi, Babatunde Ekundayo, Seun Walker



UG RA: T. Femi-Fowode & F. Obasuyi

Synopsis: Thermal batteries are primary reserve batteries that are solid state at normal temperature. They have been the first choice of power supply for guided missiles and nuclear weapons. The aim of the work is to improve the knowledge base of material property data on thermal battery insulators. For this research the material property that was evaluated was the coefficient of friction, to determine the displacement of the battery component at high stress when the missile is in operation. The coefficient of friction is used to approximate the force of friction, which is determined by the ease with which two surfaces slide against each other. The angle at which an object begins to slide down an incline, when measured is used to determine the coefficient of friction, μ . The frictional force is the force that resists the sliding motion of one surface over another. In this experiment the frictional force between the surface on the base material on the incline plane and the sample material was measured. (info>)

6 TAMU SYSTEM PATHWAY SYMPOSIUM AWARDED PROJECTS

CECSTR, P.O. Box 519, MS 2521, Prairie View, Texas 77446. All rights reserved.